



TECHNICAL SPECIFICATIONS

MACHINE

Machine type

Bore & stroke Maximum power Maximum torque

Starting system Lubrication system Fuel tank capacity

Fuel supply Transmission type Liquid cooled, 4-stroke, SOHC, 4-valve 57.0 × 58.7mm 11.0kW / 8500 rpm

13.7 Nm / 6500 rpm Electric starter and kickstarter

Wet sump 4.2L

Fuel injection

Constant mesh, 5-speed

DIMENSIONS

LxWxH 1,985mm x 670mm x 1,100mm 795mm Seat height Wheelbase 1290mm Minimum ground clearance 155mm Content weight 118ka

FRAMEWORK

Backbone Frame type Front tire 90 / 80 - 17M / C 46P Tubeless Rear tire 120 / 70 - 17M / C 58P Tubeless Front brake Hydraulic single disc brake Rear brake Hydraulic single disc brake

Front suspension Telescopic fork Rear suspension Swingarm

ELECTRICAL

Ignition system Spark plug model Battery Type

TCI (transistor controlled ignition) CR8E

GTZ4V / YTZ4V











HONG LEONG CORPORATION HOLDINGS PTE LTD

YAMAHA Showroom: 178 Paya Lebar Road #01-01/02 Singapore 409030

Tel: 6749 0588 | Fax: 6745 2749

Website: www.yamaha-motor.sg