

## MT-15



Liquid-cooled, 4-stroke,

13.9 kw at 10000 rpm

14.4 Nm at 8500 rpm

SOHC, 4-valve

58.0 x 58.7 mm

11.6 ± 0.4 : 1

Wet sump

155 cm<sup>3</sup>













Ma	act	nine	

Engine Type

Displacement Bore and Stroke

Compression Ratio Maximum Power Maximum Torque

Lubrication Starter System

Electric Fuel Tank Capacity 10 L Engine Oil Capacity 1.05 L

Transmission Constant mesh, 6-speed

Final Drive Chain

## **Dimensions & Chassis**

LxWxH

Seat Height 810 mm Wheelbase Min Ground Clearance

Wet Weight 133 kg Front Suspension

Rear Suspension Front Brake Rear Brake

Front Tire Rear Tire

1965 mm X 800 mm X 1065 mm

1335 mm 155 mm

Telescopic fork

Swingarm (link suspension) Hydraulic single disc brake Hydraulic single disc brake 110 / 70-17M / C 54S Tubeless 140 / 70-17M / C 66S Tubeless



Blue

Electrical Ignition

TCI (Transistor Controlled Ignition)



## HONG LEONG CORPORATION HOLDINGS PTE LTD

YAMAHA Showroom: 178 Paya Lebar Road #01-01/02 Singapore 409030

Tel: 6749 0588 | Fax: 6745 2749 |

Website: www.yamaha-motor.sg